



AeroFC V2

One Flight Controller. Every Drone Mission.
Compatible with Open-Source firmware and GCS.

Proudly Made in India.



About

AeroFC V2 is a next-generation, high-performance flight controller engineered to power any drone, any mission, anywhere. Designed and built in India, it brings together precision, reliability, and intelligent control to support everything from agriculture and mapping to logistics, surveillance, inspection, and custom UAV innovations. With full compatibility for any open-source firmware and ground control software, AeroFC V2 gives you complete freedom to build without restrictions.



○ Superior Processing Power

AeroFC V2 Flight Controller is powered by a high-performance main processor built on a 32-bit architecture, running at high speed. It operates alongside an efficient I/O processor to manage input and output seamlessly.



○ Advanced External Sensor Support

AeroFC V2 Flight Controller supports CAN-based front and back obstacle avoidance radars, allowing your drone to navigate complex environments with ease. Additionally, the CAN-based altimeter provides precise terrain - following capabilities, ensuring stable and accurate flights even in rugged or varied landscapes.

- CAN-Based Front and Back Obstacle Avoidance Radars
- Provides Precise Terrain-Following Capabilities



○ Broader Connectivity For Flexibility

AeroFC V2 Flight Controller offers 8 PWM outputs for motors, 4 auxiliary PWM/GPIO outputs, and 2 CAN buses, 3 UART ports for complex configurations and seamless connectivity. The dedicated R/C inputs for PPM and S. Bus signals ensure compatibility with a wide range of external systems, giving you ultimate flexibility in customizing your drone setup.

- AeroFC V2 offers 8 PWM outputs for motors
- 4 auxiliary PWM/GPIO outputs
- 2 CAN buses, 3 UART ports
- Dedicated R/C inputs for PPM and S



○ Enhanced Sensors For Precision

AeroFC V2 Flight Controller features a highly advanced sensor suite with precision accelerometers, gyroscopes, a magnetometer, and dual barometers, ensuring exceptional accuracy in motion detection, altitude, and orientation measurements.



○ Software Compatibility

AeroFC V2 offers broad and seamless compatibility with leading open-source flight-control firmware and Ground Control Station (GCS) software. It supports widely used platforms such as ArduPilot and PX4, enabling users to easily configure, customize, and update their flight systems.



Hardware Specifications:

Main Processor	STM32H7 Series 32-Bit ARM Cortex-M7 Core, 480 Mhz
Coprocessor	STM32F1 Series 32-Bit ARM Cortex-M3 Core, 72MHz
Supported RC Signals	PPM/SBUS
Connectors	Standard And Widely Used Connectors
Sensors	Triple IMU System
Sensors Details	IMU1 (Isolated) MEMS High-Impact Applications IMU3 (Isolated) High Vibration Robustness MAG 1 (Isolated) High-Precision, Ultra-Low Noise MAG2 + MAG3 (External) Supports External Magnetometer BARO1 (Isolated) High-Resolution Barometric Pressure Sensor BARO1 (On Board) High-Resolution Barometric Pressure Sensor

Specifications:

Chassis Material	Aerospace Grade Aluminum
Size	89 x 45 x 30 mm
Operating Temperature	-40°C to +85°C
Motor PWM I/Os	8
Auxiliary PWM / Digital I/Os	4
Dedicated Telemetry Interface	1
Number Of GPS Supported	2
Auxiliary UARTs	2
I2C Interface	1
CAN Interface	2
Power and Current, Voltage Measurement Interface	1
RCIN Interface	1
USB Interface	1
SDCARD Interface	1
Power and Current, Voltage Measurement Interface	1



AeroFC V2

Built in India. Engineered for the World.

The Only Flight Controller Your Drone Will Ever Need



Other Drone Products

Ag++ Flight Controller | NamoAG | AeroGCS Software Ecosystem

Order Now



6th & 7th Floor, Royale Arc Avenue, ITI Signal, Near Indian Oil Petrol Pump, Nashik - 422007
Maharashtra, India

<https://aerogcs.com/aerofc-v2/> | solutions@pdrl.in | +91 77700 13322